
IERICH


ATLAS[™] 7242

Always check the website for the most updated specifications: www.americh.com



Builder Series






28


ģ

Platinum Series






(pump and blower location only)



Airbath System II Airbath System III




N/A

LEGEND: P PUMP 🛚 🕒 BLOWER 🗢 JET 🛛 💿 ROTARY JET 上 SUCTION 🛛 👹 LIGHT ON/OFF CONTROL 🗖 GRAB BAR 🛛 🗕 - ACCESS PANEL (PROVIDED BY FACTORY)

INSTALLATION TIPS

- Install according to Owner's Manual and local codes.
- Access panel for whirlpool and Airbath[®] systems included with the Atlas.
- Hot water supply should be 65-75% of tub capacity or greater.
- · Always consult your local plumber for recommendations as installations will vary.



All bathtub dimensions are ± 1/2"

DIMENSIONS

72" x 42" x 23" (1829 x 1067 x 584 mm) Whirlpool Operating Gallons = 70 (Liters = 265) Gallon to Overflow = 105 (Liters = 397)

MATERIAL: Polymer Composite (White and Biscuit Only)

TUB FLOOR: Non-Textured

UNDERMOUNT: No

ELECTRICAL REQUIREMENTS

Americh recommends one 20 amp ground fault circuit interrupter (GFCI) for each power supply provided with the bathtub.

OPTIONAL ACCESSORIES

- Chromatherapy*
- Grab Bars: 9" * 14" 16"
- High Density Insulation*
- Inline Heater (whirlpool only)
- Jets: Additional or Rotary*
- Pillow: Angle *
 - 13" Full Back
- Remote Control Upgrade (select series only)
- Syllent Pump with Heated Air*
- Trim Kit Upgrade*
- Waste & Overflow
 - Cable Drive Overflow*
 - Linear Overflow

*Standard on Platinum Series

CODES AND COMPLIANCE

Americh products meet or exceed the following standards:

- Underwriters Laboratories (UL)
- Underwriters Laboratories Canada (cUL)
- Canadian Standards Association (CSA)
- ANSI Z124.1 ANSI A112-19.7
- ANSI A112.19.8

Contact Americh for additional approvals.