

Accessories wall holder # 100724



| wall holder | Dimension | Weight | Order number |
|--|--------------|-----------------|--------------|
| frame type, for permanent remote control fixation, suitable for SensoWash Plus remote control | | | |
| Colors | | | |
| Variant | | | |
| Installation accessories | | | |
| SensoWash® Starck f Plus compact shower toilet Rear-, Lady- and Comfortwash, Seat heating, Intelligent energy saving mode, Warm air dryer, individual adjustment of water-, air- and seat temperature as well as spray wand position and water spray intensity, Automatic drainage in periods of prologed disuse, Descaling function, Night light, rimless, Remote control included, washdown model, App operation, Self-cleaning spray wand, with concealed connections | 378 x 575 mm | 32.500 kilogram | 650000 |
| SensoWash® Starck f Plus shower toilet seat Rear-, Lady- and Comfortwash, Seat heating, Warm air dryer, individual adjustment of water-, air- and seat temperature as well as spray wand position and water spray intensity, Night light, Intelligent energy saving mode, Remote control included, App operation, Self-cleaning spray wand, Descaling function, Automatic drainage in periods of prologed disuse | 378 x 574 mm | 7.000 kilogram | 612000 |
| SensoWash® i Plus integrated shower toilet Rear-, Lady- and Comfortwash, vertical outlet, Seat heating, Intelligent energy saving mode, Warm air dryer, individual adjustment of water-, air- and seat temperature as well as spray wand position and water spray intensity, Odor extraction, Automatic odor extraction, Adjustable odor extraction follow-up time, Auto flush, with integrated flushing system, Pre-flushing, Automatic opening/closing of lid, Electromotive actuated lid, Descaling function, Night light, 2 individually programmable user profiles, Remote control included, App operation, Self-cleaning spray wand, on / off-button | 366 x 683 mm | 48.000 kilogram | 620000 |

All drawings contain the necessary measurements which are subject to standard tolerances. They are stated in mm and are non-binding. Exact measurements, in particular for customised installation scenarios, can only be taken from the finished piece.